



12/9/2011

The Clorox Company
1221 Broadway
Oakland, CA 94612
Tel. (510) 271-7000

PRO-Strength Liquid PLUMR
Material Safety
Data Sheet

I Product: PRO-STRENGTH LIQUID-PLUMR® WITH PENETREX™

Description: CLEAR ALKALINE LIQUID WITH A CHLORINE ODOR

Other Designations

Drain Cleaner
Drain Opener

Distributor

Clorox Sales Company
1221 Broadway
Oakland, CA 94612

Emergency Telephone Nos.

For Medical Emergencies call:
(800) 446-1014
For Transportation Emergencies Chemtrac
(800) 424-9300

II Health Hazard Data

CAN CAUSE BURNS ON CONTACT. Injures eyes, skin and mucous membranes on contact. Harmful if swallowed; nausea, vomiting, and burning sensation of the mouth and throat may occur. No adverse health effects are expected with recommended use. Occasional clinical reports suggest a low potential for sensitization upon exaggerated exposure to sodium hypochlorite if skin damage (eg. irritation) occurs during exposure. However, clinical tests conducted on intact skin with products containing sodium hypochlorite found no sensitization in the test subjects.

Although not expected, heart conditions or chronic respiratory problems such as asthma, chronic bronchitis or obstructive lung disease may be aggravated by exposure to high concentrations of vapor or mist.

FIRST AID:

EYE CONTACT: Flush immediately with water for 15 minutes. If wearing contact lenses, remove after first 5 minutes. Immediately contact a doctor.

INGESTION: Drink a glassful of water. **DO NOT** induce vomiting. Immediately contact a doctor or Poison Control Center.

SKIN CONTACT: Remove contaminated clothing. Wash immediately with water. Contact a doctor immediately if irritation or discomfort persists.

INHALATION: Remove from exposure to fresh air.

III Hazardous Ingredients

Ingredient	Concentration	Worker Exposure Limit
Sodium hypochlorite CAS #7681-52-9	5-10%	not established
Sodium hydroxide CAS # 1310-73-2	1- 2.5%	2 mg/m ³ - TLV-C 2 mg/m ³ - PEL-TWA
Myristamine Oxide CAS# 3332-27-2	0.5-2.0%	not established
Lauramine oxide CAS# 1643-20-5)	0.5-2.0%	not established

TLV-C = ACGIH Threshold Limit Value - Ceiling

PEL-TWA = OSHA Permissible Exposure Limit - Time Weighted Average/Short Term Exposure Limit

None of the ingredients in this product are on the IARC, OSHA or NTP carcinogen lists.

IV Special Protection and Precautions

Hygienic Practices: Wear safety glasses and gloves. The availability of an eye wash and shower is recommended in a manufacturing environment.

Engineering Controls: Use general ventilation to minimize exposure to vapors.

Work Practices: Avoid splashing, eye and skin contact and inhalation of vapor or mist.

KEEP OUT OF REACH OF CHILDREN. Avoid all splashing; particularly in eyes, on skin and clothing. Keep children away from basins containing Pro-Strength Liquid-Plumr. Do not use plunger with Pro-Strength Liquid-Plumr. Do not use Pro-Strength Liquid-Plumr with ammonia, toilet bowl cleaners or other drain openers. Do not reuse empty container. Rinse container and replace cap before discarding.

V Transportation and Regulatory Data

U.S. DOT Hazard Class: Consumer Commodity ORM-D

IMDG: Dangerous goods in limited quantities of Class 8.

IATA: Corrosive liquid, n.o.s., Class 8, Packing Group II.

EPA - SARA TITLE III/CERCLA: This product is not reportable under Sections 311/312 and contains no chemicals reportable under Section 313. This product does contain chemicals (sodium hydroxide and sodium hypochlorite) that are regulated under Section 304/CERCLA.

TSCA/DSL STATUS: All components of this product are on the Canadian DSL; and, are either on the TSCA 8(b) Inventory or otherwise exempt from listing. This product is not subject to TSCA 12(b) reporting requirements.

VI Spill Procedures/Waste Disposal

Spill Procedures: Absorb and containerize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material.

Waste Disposal: Dispose of in accordance with all applicable federal, state, and local regulations.

VII Reactivity Data

Stable under normal use and storage conditions. Reacts with other household chemicals such as toilet bowl cleaners, ammonia or other drain openers to produce hazardous gases, such as chlorine and other chlorinated species.

VIII Fire and Explosion Data

Not flammable or explosive.

IX Physical Data

Boiling point approx. 212 °F/100 °C
Specific Gravity (H₂O=1) 1.08 - 1.11
Solubility in Water complete
pH ~13